



MODEL	FILL	PAN ID	DEPTH	CAPACITY
850-4-100P	4" FPT	15"	14"	10 GAL
850-3-100P	3" FPT	15"	14"	10 GAL
850-4-120P	4" FPT	15"	16"	12 GAL
850-3-120P	3" FPT	15"	16"	12 GAL
850-4-150P	4" FPT	17"	16"	15 GAL
850-3-150P	3" FPT	17"	16"	15 GAL
850-4-160P	4" FPT	17"	17"	16 GAL
850-3-160P	3" FPT	17"	17"	16 GAL

- MATERIALS:**
- **PAN:**
CARBON STEEL, 14GA MIN
 - **LID:**
CARBON STEEL, 16GA MIN (ALT 5052-H32 ALUMINUM)
 - **HINGE ASSY:**
CARBON STEEL, 10GA
PIN: 5/16" DIA ZINC PLATED
NUT: 5/16"-18 NYLOC, ZINC PLATED
 - **HANDLE:**
1/8" X 1" FB STEEL (ALT 5052-H32 ALUMINUM)
 - **LOCK TAB:**
1/8" X 1" FLAT BAR STEEL
 - **FILL/DRAIN FITTING:**
SCH 40 STEEL (MIN)
 - **DRAIN PLUG ASSY:**
3/8" DIA STEEL ROUND BAR WELDED TO 1/2" MPT STEEL PIPE PLUG
 - **COATING:**
POWDERCOAT EPOXY FINISH INT/EXT
- CAUTION**
- FLAMMABLE OR COMBUSTIBLE LIQUIDS/VAPORS MAY BE PRESENT. KEEP AWAY SPARKS, FLAME, IGNITION SOURCES. EXTINGUISH SMOKING MATERIALS. FOR USE ONLY ON PROPERLY VENTED ABOVEGROUND STORAGE TANKS. KEEP LID CLOSED AND OPENINGS SECURELY PLUGGED EXCEPT DURING ACTUAL TANK FILLING.

HINGE ASSEMBLY DESTAIL
Die stamped hinge assy. and positive "lip stop" tabs

This drawing and design are proprietary to **BAKER INDUSTRIES NORTHWEST**, and may not be copied or duplicated in whole or in part without the written permission of **BAKER INDUSTRIES NW**.

#800 SERIES TANK TOP SPILL CONTAINMENT FOR ABOVEGROUND TANKS

BAKER INDUSTRIES NORTHWEST
12428 Highway 99 South, Unit 56
Everett, Washington 98204-5502
Tel: (425) 212-3169 • FAX: (425) 353-6788 • e-mail: larry@bakerindnw.com
www.bakerindustriestnorthwest.com

REV	DESCRIPTION	DRAWN	CHECKED	DATE
REV		KF	LRG	10-03-92
REV		KF	LRG	01-07-93
REV		SLG	LRG	03-05-06

